

90 Metre Mobil Sepetli Personel Yükseltici Platform

**Ege'de ilk-90M
Yükselticili Platform**

BRONTO | SKYLIFT **S90 HLA**

BRONTO | SKYLIFT S90 HLA

Optional Equipment

- Extendable working cage with hydraulic extension up to 3,7 meters
- CW-400, detachable winch in the working cage 400 kg and winch arm slewing ± 45 degrees (only for materials)
- BW-1100, boom winch mounted in the end of the 1 st boom (mechanical structure, electricity and winch). Capacity 1100 kg. (only for materials)
- Ultrasonic collision guard, 4 sensors
- B-RCC, Rotating camera cage
- Element lifting system. 1 pc capacity 150 kg
- Lighting rig, capacity 30 kg
- B-WRC Wireless Remote Control
- A 6,5 kVA (230V / 400 V / 50Hz) hydraulically driven generator.
- Bronto Loadman, portable device for measuring the bearing capacity of ground.
- Electric motor drive for the hydraulics
- Round ground pads.

Technical data

- Max. working height 90 m
- Max. outreach 32,6 m
- Max up and over 28 m
- Max. cage load 700 kg
- Extendable cage 600 kg
- Typical chassis GVW 48 t
- Max. permitted wind speed 12,5m/s

Features

- Automatic levelling
- Easy and precise control system
- Variety of optional equipment
- Spare part available for at least 25 years
- Bronto Compass remote diagnostics

